



SURFboard® SB6120

Cable Modem

Strengthen your broadband leadership — Count on Motorola's SURFboard DOCSIS® / EuroDOCSIS 3.0 CPE to help you deliver innovative, ultra broadband data services to your premium customers.

Highlights

Compatible with Windows®, Macintosh®, and UNIX® computers

DOCSIS 3.0 and EuroDOCSIS 3.0 Certified, featuring:

- Channel bonding of up to 4 downstream channels and 4 upstream channels increasing data rates of well over 100 Mbps in each direction
- Supports IPv4 and IPv6 to expand network addressing capabilities
- Enhanced security: supports AES traffic encryption

Enhanced network management

Ability to provision and manage IP multicast

GigE (RJ-45) data port with Auto Negotiate and Auto MDIX

Front Panel LEDs indicate status and simplify troubleshooting

User-friendly online diagnostics

Remotely configurable and monitorable using SNMP and TFTP

High Value and Increased Data Rates

Motorola's easy-to-use SB6120 SURFboard DOCSIS 3.0 Cable Modem unlocks the potential of offering innovative high-bandwidth data and multimedia services to customers.

Utilizing the power of DOCSIS 3.0, the SB6120 enables channel bonding of up to 4 downstream channels and 4 upstream channels – which allows an operator to offer their customers advanced multimedia services with data rates of well over 100 Mbps in each direction. The SB6120's higher-speed services enable operators to:

- Protect their installed base of high-speed data customers
- Deliver high-bandwidth, multimedia services
- Deliver competitive, high-capacity commercial services to their business customers

Economic and Flexible

The Motorola SB6120 SURFboard DOCSIS 3.0 Cable Modem provides operators with an economic option for providing Ultra-Broadband services, with 4X the current maximum user data throughput approximating 160 Mbps in DOCSIS mode and 195 Mbps in EuroDOCSIS mode*, without the need for hybrid fiber coax (HFC) plant upgrade. Maximizing an operator's current infrastructure investment, the SB6120 can be deployed without service interruption.

Backwards compatible to DOCSIS 1.0, 1.1 and 2.0, the SB6120 also supports both IPv4 and IPv6, Advanced Encryption Services, and all other DOCSIS 3.0 standards.

As part of Motorola DOCSIS 3.0 Ultra-Broadband family of products, the SB6120 includes an enhanced tuner that supports up to a 1 GHz downstream input allowing operators to increase the frequency spectrum for deployment of new high-value services such as bandwidth on-demand, commercial services, interactive gaming and IPTV to their customers.

The SB6120 features a 10/100/1000Base-T Ethernet (RJ-45) port, as well as intuitive, easy to read front-panel operational status LEDs. Operators can optionally activate dual colored LEDs for their customer to have visual verification of bonded channels and GigE link use.

With Motorola's cable modems, high-speed Internet access has always been at your fingertips – always on and always connected. The SB6120 is the ideal competitive solution for the high-end residential user, the small home office owner, as well as the medium to large business enterprise.



Motorola's SB6120 SURFboard® Cable Modems are helping service providers lower their carbon footprint by helping them lower energy consumption. Motorola has a global commitment to be part of the solution to climate change, working for years to continually improve the environmental profile of our products, operations and supply chain. We are in step with our customers and their increasing interest in partnering with a company that will help them reduce their environmental impact, while offering compelling products that will help them grow their eco-conscious customer base.

Motorola designed the next generation SURFboard portfolio of customer premises equipment (CPE) to minimize its impact on the environment. Motorola's CPE comply with international environmental and energy efficient standards. The portfolio uses ENERGY STAR qualified power supplies and its devices and power supplies are compliant with European Code of Conduct regulations. In addition, the devices and power supplies are lead-free and RoHS compliant. Finally, all new SB6120 SURFboard Cable Modems use environmentally friendly package designs. The SB6120 cable modems are available in single bulk pack boxes – eliminating the use of suspension plastic and reducing box size – thereby reducing waste and transport costs. Motorola SB6120 cable modem's packaging is 100% recyclable and is marked with standard recycling codes to make it easier for our customers to identify recycling opportunities.

Motorola's Service Assured DOCSIS® 3.0 Solutions enable you to deliver increased bandwidth, enhance security, and cost-effectively deploy data services to your bandwidth-demanding consumers — all while maximizing current infrastructure investment and lowering capital spend.

General Specifications

Cable Interface	75 Ω F-connector
CPE Network Interface	10/100/1000Base-T Ethernet (RJ-45)
Data Protocol	TCP/IP
Dimensions	5.7 in H x 5.7 in W x 1.5 in D (146 mm x 146 mm x 38 mm)
Power	9W (nominal)
Input Power	
North America	105 to 125 VAC, 60 Hz
Outside North America	100 to 240 VAC, 50 to 60 Hz
Regulatory	Unit is RoHS compliant, ENERGY STAR V2 , COC V3, Compliant per the "Code of Conduct on Energy Consumption of Broadband Equipment", CMM, MEPS

Environmental

Operating Temperature	32 °F to 104 °F (0 °C to 40 °C)
Storage Temperature	-22 °F to 158 °F (-30 °C to 70 °C)
Operating Humidity	5 to 95% R.H. (non-condensing)

Downstream

Modulation	64 or 256 QAM
Capture Bandwidth	100 MHz (edge to edge)
Maximum Theoretical Data Rate**	
DOCSIS	171.537 Mbps (4 channels) / 42.884 (single channel) @ 256 QAM at 5.36 Msym/s
EuroDOCSIS	222.464 Mbps (4 channels) / 55.616 (single channel) @ 256 QAM at 6.952 Msym/s
Bandwidth	
DOCSIS	≤ 24 MHz
EuroDOCSIS	≤ 32 MHz
Symbol Rate	
DOCSIS	64 QAM 5.057 Msym/s; 256 QAM 5.361 Msym/s
EuroDOCSIS	64 QAM 6.952 Msym/s; 256 QAM 6.952 Msym/s
Operating Level Range	-15 to 15 dBmV
Bonded Channel RF Level Tolerance	10dBmV
Input Impedance	75 Ω (nominal)
Frequency Range	DOCSIS and EuroDOCSIS 108 to 1002 MHz (edge to edge), Optional 91 to 1002 MHz (edge to edge)
Frequency Plan	
EuroDOCSIS	Annex A
DOCSIS	Annex B
J-DOCSIS	Annex B, modified for Japan Frequencies
Security	DOCSIS 3.0 Security (BPI+, EAE, SSD)
Network Management	SNMP v2 & v3
Provisioning	Supports IP addressing using IPv4 and/or IPv6 (dual stack)



Upstream

Modulation	QPSK and 8, 16, 32, 64, 128 QAM
Maximum Channel Rate**	
DOCSIS	131.072 Mbps (4 channels) / 32.768 Mbps (single channel): @ 128 QAM at 6.4 MHz
EuroDOCSIS	131.072 Mbps (4 channels) / 32.768 Mbps (single channel): @ 128 QAM at 6.4 MHz
Channel Width	200 kHz, 400 kHz, 800 kHz, 1.6 MHz, 3.2 MHz, 6.4*** MHz
Symbol Rates	160, 320, 640, 1280, 2560, 5120**** ksym/s
Operating Level Range	Level range per channel (Multiple Transmit Channel mode disabled, or only Multiple Transmit Channel mode enabled with one channel in the TCS)
DOCSIS/EuroDOCSIS	
TDMA	Pmin to +57 dBmV (32 QAM, 64 QAM) Pmin to +58 dBmV (8 QAM, 16 QAM) Pmin to +61 dBmV (QPSK)
S-CDMA	Pmin to +56 dBmV (all modulations), where: Pmin = +17 dBmV, 1280 kHz modulation rate Pmin = +20 dBmV, 2560 kHz modulation rate Pmin = +23 dBmV, 5120 kHz modulation rate
Level range per channel (two channels in the TCS)	
TDMA	Pmin to +54 dBmV (32 QAM, 64 QAM) Pmin to +55 dBmV (8 QAM, 16 QAM) Pmin to +58 dBmV (QPSK)
S-CDMA	Pmin to +53 dBmV (all modulations), where: Pmin = +17 dBmV, 1280 kHz modulation rate Pmin = +20 dBmV, 2560 kHz modulation rate Pmin = +23 dBmV, 5120 kHz modulation rate
Level range per channel (three or four channels in the TCS)	
TDMA	Pmin to +51 dBmV (32 QAM, 64 QAM) Pmin to +52 dBmV (8 QAM, 16 QAM) Pmin to +55 dBmV (QPSK)
S-CDMA	Pmin to +53 dBmV (all modulations), where: Pmin = +17 dBmV, 1280 kHz modulation rate Pmin = +20 dBmV, 2560 kHz modulation rate Pmin = +23 dBmV, 5120 kHz modulation rate
Output Impedance	75 Ω (nominal)
Frequency Range	DOCSIS 5-42 MHz (edge to edge), EuroDOCSIS and optional DOCSIS 5 to 65 MHz (edge to edge)
Compatibility	PC: 90496, Pentium, or later; Windows Vista™, 2000, or XP or Linux® with Ethernet connection (older versions of Windows, although not specifically supported, will work with this cable modem) Macintosh: Power PC or later; OS 9 or higher, Ethernet connection UNIX: Ethernet connection Home Networking: Ethernet router or wireless access point

* Actual speeds will vary, and are often less than the maximum possible. Data transmission speed is approximate and depends on the configuration and capacity of your network, as well as the amount of traffic on the network.

** Actual data throughput will be less due to physical layer overhead (error correction coding, burst preamble, and guard interval).

*** With A-TDMA- or S-CDMA-enabled CMTS.

**** With S-CDMA-enabled CMTS.

Certain features may not be activated by your service provider, and/or their network settings may limit the feature's functionality. Additionally, certain features may require a subscription. Contact your service provider for details.

All features, functionality, and other product specifications are subject to change without notice or obligation. DOCSIS 3.0 modem capabilities are dependant on the services available through the CMTS. Please verify with your CMTS vendor their specific DOCSIS 3.0 implementation roadmap.



Motorola, Inc. www.motorola.com



Powered by an ENERGY STAR® qualified adapter for a better environment

MOTOROLA and the Stylized M Logo are registered in the US Patent & Trademark Office. SURFboard is a registered trademark of General Instrument Corporation, a wholly-owned subsidiary of Motorola, Inc. Windows is a registered trademark and Vista is a trademark of Microsoft Corporation in the U.S. and/or other countries. Linux is a registered trademark of Linus Torvalds. UNIX is a registered trademark of the Open Group in the United States and other countries. Macintosh is a registered trademark of Apple Computer, Inc. ENERGY STAR is a registered mark owned by the U.S. government. DOCSIS is a registered trademark of Cable Television Laboratories, Inc. All other product or service names are the property of their respective owners. © Motorola, Inc. 2009 All rights reserved.